

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**Amendments to the Claims:**

This listing of claims replaces all prior versions, and listings, of claims in this application.

**Listing of Claims:**

41. (Currently Amended) A method for shaping web materials comprising the steps of:

(a) feeding a web material between a rotary die and an anvil roller, wherein the rotary die and the anvil roller are rotating in opposite directions;

(b) cutting the web material with the rotary die into a web product and a web flash;

(c) conveying the web product away from the anvil roller; and

(d) removing the web flash for recycling;

(e) adhering the web product to the rotary die;

(f) rotating the web product around the rotary die to the bottom of the rotary die;

(g) feeding a primary web material between the rotary die and a second anvil roller,

wherein the rotary die and the second anvil roller are rotating in opposite directions;

(h) joining the web product and the primary web material at a location between the rotary die and the second anvil roller;

(i) cutting the primary web material with the rotary die into a primary web product and a primary web flash, wherein the primary web product is equal in size and shape to the web product and is attached to the web product to form a final product;

(j) conveying the final product away from the rotary die and the second anvil roller;  
and

(k) removing the primary web flash for recycling.

42. (Original) The method of claim 41, wherein the step of feeding a web material comprises conveying the web material on a vacuum belt.

43. (Original) The method of claim 41, wherein the step of conveying the web product away comprises conveying the web product on a vacuum belt.

44. (Original) The method of claim 41, wherein the step of removing the web flash comprises conveying the web flash on a belt.

45. (Original) The method of claim 41, wherein the step of removing the web flash further comprises applying lubricant to the rotary die to ease removal of the web flash from the rotary die.

46. (Original) The method of claim 41, wherein the web material comprises more than one layer and the anvil roller is configured to produce a kiss-cut, wherein the rotary die cuts only one layer of the web material.

47. (Original) The method of claim 46, wherein the web material comprises a product layer and a liner, and wherein the rotary die cuts only the product layer into the web product and the web flash.

48. (Original) The method of claim 47, wherein the product layer comprises at least one mastic and the liner comprises at least one member selected from the group consisting of paper, polyethylene, polyester, aluminum foil, brass foil, and copper foil.

49. (Original) The method of claim 47, wherein the product layer comprises rubber butyl based mastic and the liner comprises rubber butyl web.

50. (Original) The method of claim 41, wherein the anvil roller is configured to produce a through-cut.

51. Cancel

52. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of feeding the primary web material comprises conveying the primary web material on a vacuum belt.

53. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of conveying the final product away comprises conveying the final product away on a vacuum belt.

54. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of removing the web flash comprises conveying the web flash on a belt.

55. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of removing the web flash comprises vacuuming the web flash off of the anvil roller.

56. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of removing the primary web flash comprises conveying the primary web flash on a belt.

57. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of removing the web flash further comprises applying lubricant to the rotary die to ease removal of the web flash from the rotary die.

58. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of removing the primary web flash further comprises applying lubricant to the rotary die to ease removal of the primary web flash from the rotary die.

59. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of adhering the web product to the rotary die comprises applying a vacuum through the rotary die.

60. (Currently Amended) The method of claim ~~54~~ 41, wherein the step of adhering the web product to the rotary die comprises applying temporary adhesive to the rotary die.

61. (Currently Amended) The method of claim ~~51~~ 41, wherein the web material comprises one of a mastic, a polyethylene, a polyester, and a metal foil, and wherein the primary web material comprises one of a mastic, a polyethylene, a polyester, and a metal foil.

62. (Currently Amended) The method of claim ~~51~~ 41, wherein the rotary die and the anvil roller are mounted on a lifting mechanism, wherein a second rotary die and a second anvil roller are mounted on a second lifting mechanism in a raised position, and wherein the method further comprises the steps of:

- (e) lifting the rotary die and the anvil roller out of service;
- (f) lowering the second rotary die and the second anvil roller;
- (g) feeding additional web material between the second rotary die and the second anvil roller, wherein the second rotary die and the second anvil roller are rotating in opposite directions;
- (h) cutting the additional web material with the second rotary die and the second anvil roller into additional web product and additional web flash;
- (i) conveying the additional web product away from the second rotary die and the second anvil roller; and
- (j) removing the additional web flash for recycling.

63. (Currently Amended) The method of claim ~~51~~ 41, wherein the rotary die, the anvil roller, and the second anvil roller are mounted as a first assembly on a lifting mechanism,

wherein a second assembly including a second rotary die, a third anvil roller, and a fourth anvil roller is mounted on a second lifting mechanism in a raised position, and wherein the method further comprises the steps of:

- (l) lifting the first assembly out of service;
- (m) lowering the second assembly; and
- (n) repeating steps (a) through (k) using the second assembly.

64-77. Cancel

78. (Original) The method of claim 41, wherein the web product comprises a mastic and a film.

79. (Previously Presented) The method of claim 41, wherein the web material comprises polyester.

80. (Previously Presented) The method of claim 41, wherein the web product comprises an automotive sealant.